

SYBTU2-PLP

APC Symmetra PX 9Ah Battery Unit, High Performance



Overview

Presentation	For Symmetra PX 100, it is recommended to replace all four batteries in a row at the same time to ensure optimal runtime. If you are ordering this battery unit for a Symmetra PX 100, you must order battery units in multiples of 2 and you must replace string positions A+B or C+D, as the batteries are connected in pairs. The batteries in each half string must be from the same manufacturer. For Symmetra PX 250/500, it is recommended to replace all six batteries in a row at the same time to ensure optimal runtime. If you are ordering this battery unit for a Symmetra PX 250/500, you must order battery units in multiples of 3 and you must replace the batteries in string position A+B+C or D+E+F, as they are connected in pairs. The batteries in each half string must be from the same manufacturer.
Lead time	Usually in Stock

General

Provided equipment	Installation guide
--------------------	--------------------

Physical

Color	Black
Depth	27.56 in (70 cm)
Height	6.26 in (15.9 cm)
Net Weight	55.56 lb(US) (25.2 kg)
Width	4.21 in (10.7 cm)

Conformance

Product certifications	CE
Standards	UL 1778

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 ft (0.00...4572.00 m)

Ordering and shipping details

GTIN	00731304242529
Package weight(Lbs)	59.52 lb(US) (27 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Height	7.09 in (18 cm)
Package 1 width	5.91 in (15 cm)
Package 1 Length	31.89 in (81 cm)
Number of Units in Package 3	32

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------