

### Main

Device short name	C
Disconnecter device type	Thermal magnetic circuit breaker

### Complementary

Depth	9.63 in (244.60 mm)
Device mounting	Surface
Height	35 in (889.00 mm)
Maximum Horse Power Rating	20 hp 460/575 V AC
NEMA size	2
Number of poles	3
Number of thermal units required	6
Width	20.38 in (517.65 mm)

### Environment

NEMA degree of protection	NEMA 1
---------------------------	--------

### Ordering and shipping details

Category	21401 - 8941 DUPLEX MOTOR CONTROLLERS
Discount Schedule	CP1
Nbr. of units in pkg.	1
Package weight(Lbs)	70 lb(US) (31.75 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Under investigation

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.