

Datasheet

RS PRO IP67 M16 DIN PLUG SCREW LOCK

Stock No: 2100226 , 2100229 , 2100232 , 2100222 , 2100234



Technical Specifications:

To include attributes e.g. height, width, depth, color etc.

Connector type:	Plug
Mounting type:	Cable
IP Rating:	IP67
Contact Gender:	Male
Number of Contact::	3 - 8

Features & Benefits:

-
-
-
-

Dimensional line drawings

See examples on Brandzone

REF. 88.7

CABLE 08.65-7.2

1. MATERIAL :

- 1-1. HOUSING : NYLON UL94V-0 ; COLOR : BLACK
- 1-2. CONTACT : BRASS
- 1-3. MAIN BODY : ZINC ALLOY
- 1-4. LOCK SHELL : BRASS
- 1-5. SPRING : STAINLESS
- 1-6. ISOLATION : PVC
- 1-7. CLAMPS : ZINC ALLOY
- 1-8. CLAMP BODY : ZINC ALLOY
- 1-9. SCREW : BRASS
- 1-10. BACK BODY : BRASS
- 1-11. O-RING : EPDM ; COLOR : BLACK
- 1-12. ISLAND : SILICONE COLOR : BLACK
- 1-13. ISLAND GAGE : POM ; COLOR : WHITE
- 1-14. ISLAND NUT : ALUMINUM ALLOY

2. FINISH :

- 2-1. CONTACT : GOLD FLASH
- 2-2. MAIN BODY : NICKEL PLATED
- 2-3. LOCK SHELL : NICKEL PLATED
- 2-4. CLAMPS : NICKEL PLATED
- 2-5. CLAMP BODY : NICKEL PLATED
- 2-6. SCREW : NICKEL PLATED
- 2-7. BACK BODY : NICKEL PLATED
- 2-8. ISLAND NUT : STAINING NICKEL PLATED

3. ELECTRICAL SPECIFICATION :

- 3-1. Rated current : 5A
- 3-2. Rated Voltage : 250V
- 3-3. Water proof : IP67

4. Environment :

- 4-1. Operation Temperature : -20 ~ 85°C

MP1603PA	MP1604PA	MP1605PA	MP1606PA	MP1607PA	MP1608PA	MP1609PA	MP1610PA

Quality Standards



General

Extra page for more complex products