



Data sheet

RS PRO Soldering station, LCD screen, 65W, 230V, 200°C- 450°C

Stock No. 202-4487

EN



Features:

- Automatic standby, shutdown with smart time setting.
- Beep alarm function available.
- Temperature locking, temperature calibration and temperature alarming function.
- Password protecting function and temperature unite switching function
- MCU controlled temperature calibration.
- New design with LCD display screen making control visualization.
- Buttons(1,2,3) for pre-setting or switching frequently used temperature.
- Including EU power cord and UK Adaptor.

Specifications:

Model	2024487			
Power consumption	65W			
Input voltage	230VAC ±10% 50Hz			
Output voltage	24VAC			
Temperature range	200~450°C(392 ~842°F)			
Temperature offset range	±50°C(±90°F)			
Temperature stability	±1°Q(still air, no load)			
Temperature accuracy	±10°C			
Temperature adjustment	Buttons			
Heater	Pluggable Four core ceramic heater			
Tip-to-ground impedance	< 2Ω			
Tip-to-ground potential	< 2mV			
Dimensions	L210*W88*H150mm			
Net weight	Approximately 2KG			

Packing List

2024487 main unit	1pc
Soldering iron (202-4488)	1pc
Iron holder (with copper wire ball)	1set
Manual	1сору
Grounding wire	1pc

EU Plug and UK Adaptor









rspro.com

Accessories:Optional Soldering Tips:

Optional Soldering			1	Tip Length	T
SKU	Description	Туре	Size	(mm)	Tip Dimensions (mm)
7998976	Soldering tip, Long Conical,0.008ln/0.2 mm	Straight conical	0.008" (0.2mm)	25mm /0.98ln	R0.2(0.008) 25(0.98)
7998989	Soldering tip,Single Flat,0.08ln/2mm	Straight hoof	0.08" (2mm)	17mm/0.68In	© 0 17(0.66)
7998973	Soldering tip,Screwdriver,0.09 4ln/2.4mm	Straight chisel	0.094" (2.4mm)	17mm/0.68In	0.5(0.02) 17(0.66)
7998982	Soldering tip,Screwdriver,0.12 6In/3.2mm	Straight chisel	0.126" (3.2mm)	17mm/0.68In	© 20 (0.25) (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.50 (0.25) (0.25) (0.50 (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25) (0.25)
7998985	Soldering tip,Screwdriver,0.03 1In/0.8mm	Straight chisel	0.031" (0.8mm)	17mm/0.68In	(a) (a) (a) (b) (a) (a) (b) (a) (a) (a) (a) (a) (a) (a) (a) (a) (a
7998979	Soldering tip,Screwdriver,0.04 7ln/1.2mm	Straight chisel	0.047" (1.2mm)	17mm/0.68In	(a) G (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c
2024516	Soldering tip, Screwdriver,0.06ln/1 .6mm	Straight chisel	0.06" (1.6mm)	17mm/0.68In	(a) (c) (a) (c) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d
2024517	Soldering tip,Single Flat, 0.02ln/0.5mm	Straight hoof	0.02" (0.5mm)	15mm/0.6ln	② (§ (°) (§ (§ (§ (§ (§ (§ (§ (§ (§ (§ (§ (§ (§
2024518	Soldering tip,Single Flat, 0.02ln/0.8mm	Straight hoof	0.02" (0.8mm)	17mm/0.66In	(S ∞) (
2024520	Soldering tip,Single Flat, 0.04ln/1mm	Straight hoof	0.04" (1mm)	15mm/0.6ln	© (5) (60) (15(0.6)
2024521	Soldering tip, straight conical, 0.008In/0.2mm	Straight conical	0.008" (0.2mm)	17mm/0.64ln	R0.2(0.008)
2024522	Soldering tip, straight conical, 0.008In/0.2mm	Straight conical	0.008" (0.2mm)	14mm/0.55In	(a) (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c
2024523	Soldering tip, straight conical, 0.02In/0.5mm	Straight conical	0.02" (0.5mm)	17mm/0.66In	R0.5(0.02)
2024524	Soldering tip, straight knife, 0.02ln/0.5mm	Straight knife	0.02" (0.5mm)	15mm/0.6ln	© 9
2024526	Soldering tip, straight knife, 0.2In/5mm	Straight knife	0.2" (5mm)	15mm/0.6ln	(1) (1) (1) (2) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1
2024527	Soldering tip, straight conical, 0.008In/0.2mm	Straight conical	0.008" (0.2mm)	13mm/0.51ln	80.2(0.008) 13(0.51)
2024528	Soldering tip,Single Flat, 0.1In/3mm	Straight hoof	0.1" (3mm)	17mm/0.66ln	€ \$\frac{1}{2}\$\$\frac{1}{45}\$\$\frac{17(0.66)}{17(0.66)}\$\$
2024529	Soldering tip,Single Flat, 0.16ln/4mm	Straight hoof	0.16" (4mm)	17mm/0.66ln	(S) (S) (A5) (17 (0, 66)
2024530	Soldering tip, bent conical, 0.008ln/0.2mm	Bent conical	0.008" (0.2mm)	12mm/0.47ln	\(\sqrt{60}\)

2024532	Soldering tip, straight knife, 0.08ln/2mm	Straight knife	0.08" (2mm)	14mm/0.55ln	2 14
2024533	Soldering tip, bent conical, 0.02ln/0.5mm	Bent conical	0.02" (0.5mm)	18.3mm/0.72ln	(D) 1532-

Optional Soldering Iron:

SKU	2024488
Description	RS PRO Soldering Iron for 2024487
Picture	