

Eaton XT IEC large contactor

DILM32-10(24V60HZ)

Dimensions:

- **Height:** 3.3 IN
- **Length:** 1.8 IN
- **Width:** 3.8 IN

Weight: .92 LB

Notes: Screw terminals (6-65A); 5 mm (80-150A);
no lugs (185-2000A)

Warranties:

- 1 year

Specifications:

- **Amperage Rating:** 32A
- **Coil:** 24V 60 Hz
- **Coil Voltage:** 24 Vac, 60 Hz
- **Contact Configuration:** 1NO
- **Frame Size:** 45 mm
- **Frequency Rating:** 60 Hz
- **Max Hp Rating:** 2, 5/ 10, 10, 20, 25 (1/3PH @120,240/208,240,480,600 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing miniature contactor
- **Wattage:** 15 kW

Supporting documents:

- [Global Data Sheet - DILM32-10\(24V60HZ\)](#)
- [Eaton Specification Sheet - DILM32-10\(24V60HZ\)](#)

Certifications:

- IEC 60947
- UL Listed
- CSA Certified

- EN 60947

Product compliance:

- RoHS Compliant
- CE Marked

© 2016 Eaton. All rights reserved.