# **UNIPAK**, Low Voltage Fixed Capacitor Banks

### 123PMURF

UPC:782116058204

## **Dimensions:**

Height: 17.3 INLength: 5.254 INWidth: 8.5 IN

Weight:18 LB

**Notes:**Multiply the 240V kVAR rating by 0.75 to calculate the kVAR value at 208V.

#### Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

## **Specifications:**

• Type: UNIPAK

Amperage Rating: 2.40AEnclosure: NEMA 1, 3R

 Enclosure Material: 14 ga. steel finished w/durable powder coat finish

• Frame Size: A1

• **Fuse Type:** Three midget-type fuses with 100,000 ampere interrupting capacity

 Indicator: Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard

• Phase: Three-phase

 Product Category: Low Voltage Fixed Capacitor Banks

• Protection: Three fuses, three lights

Rating: 1 kVAR

Voltage Rating: 240V

# **Supporting documents:**

- Eatons Volume 3-Power Distribution and Control Assemblies
- Eaton Specification Sheet 123PMURF

# **Certifications:**

- UL Listed
- CSA Certified

Product compliance: No Data

\_\_\_\_\_

© 2016 Eaton. All rights reserved.