

Eaton Type MTE industrial control transformer

CE0500E4DCEFS

UPC:786680035173

Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

Notes:Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals, Non-short circuit-proof

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** Factory-mounted finger-safe terminal shields
- **Primary Voltage:** 380/400/415V
- **Secondary Voltage:** 110/120V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** CE Marked Control Transformer
- **Volt Ampere Rating:** 500 VA

Supporting documents:

- [dry-type distribution transformer-flex center line card](#)
- [Industrial control transformers brochure](#)
- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)

- [Transformer distribution catalog, volume 2, tab 2](#)
- [Eaton Specification Sheet - CE0500E4DCEFS](#)
- [Transformer consulting application guide](#)

Certifications:

- cUL Certified
- CSA Certified
- UL Listed
- IEC 61558-2

Product compliance:

- RoHS Compliant