

Eaton pringle bolted pressure contact switch

CB2533T120480KPAXC

UPC:782116952021

Dimensions:

- **Height:** 28 IN
- **Length:** 17 IN
- **Width:** 28 IN

Weight:205 LB

Notes:OPTIONAL Ground Fault Relay, Blown Fuse Detection, Single Phase Protection, Kirk Provisions, Auxiliary Contact Provisions, AVAILABLE.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Special Features:** Interlock, single-phase voltage relay with capacitor trip device (Taylor), BFD with no lights (trips switch)
- **Type:** Pringle bolted pressure contact switch
- **Amperage Rating:** 2500A
- **Control Voltage:** 120V
- **Feed Type:** Top
- **Fuse Configuration:** Top feed
- **Ground:** No ground fault
- **Maximum Voltage:** 480V
- **Nema Rating:** NEMA 1/3R/4/12
- **Number Of Poles:** Three-pole
- **Number Of Wires:** Three-wire
- **Protection:** Fusible
- **Switch Type:** Electrical trip with charge-before-close mechanism

Supporting documents:

- [Pringle Switches - Bolted contact switches](#)
- [Installation, Operating and Maintenance Instructions for Pringle Type CBC Switches](#)
- [Custom solutions - Pringle Bolted pressure contact switches](#)
- [Eaton Specification Sheet - CB2533T120480KPAXC](#)

Certifications:

- UL Listed

Product compliance: No Data