

| REVISIONS |     |                              |           |     |      |  |  |
|-----------|-----|------------------------------|-----------|-----|------|--|--|
| REV       | ECO | DESCRIPTION                  | DATE      | BY  | APPR |  |  |
| A1        | -   | TECHNICAL DATA SHEET RELEASE | 12-MAY-14 | KMM | RFC  |  |  |

TITLE: M35 PB LITE, CLOSURE CAP, FEMALE, TRUNK

REV: A1

유





| ı | Amphenol P/N | ROCKWELL P/N | MOLEX   | TURCK   |  |  |
|---|--------------|--------------|---------|---------|--|--|
| Ī | P29043       | 889A-QMCAP   | 55-0198 | GSDM-CC |  |  |

Risk of Electrical Shock
Do Not Disconnect Under Load.
Risque de chocs electriques
Ne pas debrancher sous tension.
WARNING

|  |   | PART NUMBER |  |     | DESCRIPTION                 |  |                                      |                | IIEM  |      |   |
|--|---|-------------|--|-----|-----------------------------|--|--------------------------------------|----------------|-------|------|---|
|  | QUANTITY  |             | MATERIALS LIST   |     |                             |  |                                      |                |       |      |   |
|  | UNLESS OTHERWISE SPECIFIED  |             | SIGNATURES   |     | DATE                        | Amphon   |                                      | $\overline{A}$ |       |      |   |
|  | 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64 3 PL DEC ±0.15 Angles ±1* 3) Note reference =   MATERIAL SPECIFICATIONS:  PROCESS SPECIFICATIONS: |             | DRAWN:   | KMM | 12-MAY-14                   | Amphenol   |                                      |                |       |      |   |
|  |   |             | CHECKED:   | MRF | 12-MAY-14                   |  | Sine Systems - www.amphenol-sine.com |                |       |      |   |
|  |   |             | ENGINEER:  | KMM |                             | 44724 Morley Drive<br>Clinton Township, MI 48036 |                                      |                |       |      |   |
|  |   |             | APPROVAL:  | RFC | 12-MAY-14                   |  |                                      |                |       |      |   |
|  |   |             | CUSTOMER:  |     |                             |  | M35 PB LITE, CLOSURE CA              |                |       |      |   |
|  |   |             | THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL |     | FOR FEMALE CONNECTOR, TRUNK |  |                                      |                |       |      |   |
|  |   |             |  |     | SIZE                        | C-   | P2904                                | 43             |       | A1   |   |
|  | NEXT ASS'Y:   |             | MANUFACTURING VARIATIONS.  |     |                             | SCALE: F   | ULL                                  | C-P29043       | SHEET | 1 or | 1 |

TECHNICAL DATA:

1) MATERIALS: HOUSING: MACHINED ALUMINUM, ANODIZED

2) RoHS COMPLIANT