

4100P9W

100 Amp, 250 Volt 3-Phase, 3P, 4W, North American-Rated Pin & Sleeve Plug, Industrial Grade, IP67, Watertight - BLUE



UPC Code : 07847783895

Country Of Origin : Please Contact Customer Service.

RoHS Compliant : Yes

Technical Information

Electrical Specifications

Amperage : 100 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage : 2000V for 1 min.

Endurance : Up to 250 connects and disconnects, under load, at full rated current and voltage

Insulation Resistance : 500V for 1 min; >= 5M

Phase : 3-Phase

Pole : 3

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 250 VAC

Wire : 4

Environmental Specifications

Corrosion Resistance : Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min

Flammability : Rated V-0 per UL 94

IP Rating : IP67/IP69K

Moisture Resistance : Per UL 1682, immersed for 24 hours in 5cm of 25°C water

Material Specifications

Body Material : Valox 357

Contact Carrier : Reinforced Nylon

External Cord Clamp Assembly : Valox 357

External Screws : Acid-Proof S/S

Gland Cap : Valox 357

Grommet/Gasket : Chloroprene

Internal Cord Clamp Assembly : Thermoplastic

Internal Screws : Zinc-plated steel

Locking Ring : Valox 357

Phase and Ground Pins : Brass

Terminal Screws : Stainless Steel

Mechanical Specifications

Cable Secureness : Force: 150lb, Torque: 2.0 ft-lb, Max Disp: <= 3/32"

Cord Range : .950 - 1.875

Crush Test : 250lbs for 1 min after -25°C for 6 hrs

Impact Resistance : Drop from 30" 8 times after conditioning to -25°C for 6 hrs

Minimum Withdrawal Force : 20lbs

Product Features

Color : Blue

Configuration : North American

Device Type : Plug

Series : Standard Series

Standards and Certifications

CE Marking : Per low voltage directives 73/23/EEC, 93/68/EEC


CSA Certified : C22.2 No 182.1

IEC Rating : 60309-1 and 60309-2


UL Listed : 1682 and 1686

Warranty : 2-Year Limited

Dimensional Diagram



UNIT	A	B
inch	12.3	5.00
mm	312	127



Rated Voltage	Color
110V-130V	Yellow
125V-250V	Orange
200V-250V	Blue
277V, 380V, 440V	Grey
346V-480V	Red
500V and above	Black

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

