## Permanent Light 815 / Bulb Bulb 7W BA15D 115V



ļ

## Part No.: 955.015.37

| MECHANICAL DATA             |         |
|-----------------------------|---------|
| Height                      | 54 mm   |
| Diameter                    | 16 mm   |
| Housing colour              | Silver  |
| Weight with packaging       | 9 g     |
| Product weight              | 9 g     |
| ELECTRICAL DATA             |         |
| Operating voltage           | 115V    |
| Operating voltage frequency | 60Hz    |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage   | 115 VAC |
| Rated operational current   | 61 mA   |
| Rated inrush current        | 610 mA  |
| Power illuminant            | 7 W     |
|                             |         |
| OPTICAL DATA                | BA15d   |
| Lamp fitting/socket         | BATSU   |
| APPROVAL DATA               |         |
| Conforms with CE            | No      |
| WEEE                        | No      |
| Conforms with RED directive | No      |
| Conform with ATEX-directive | No      |
| Conforms with CCC           | No      |
| Conforms with FCC           | No      |
| Conforms with IC            | No      |
| EAC certificate available   | No      |
| Conforms with AS-I          | No      |
| ICAO Certification          | No      |
| Conforms with DNV           | No      |
| Conforms with RoHS CN       | No      |

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.