



ENGLISH

Datasheet

Stock No: 333-316

RS Pro SPDT Lever Micro switch, 4 A @ 28 V dc



Product Details

Ultra Miniature Switch

Actuator types supplied as a basic switch plus unfitted actuator kit with fixing hardware.

High switching current

Ideal where space is limited

SPDT silver-plated contacts

Contact Rating; 7A (Resistive); 4A (Inductive), 250Vac; 28Vdc

Operating temperature range: -54 to +121°C

Miniature & Subminiature

Switch type:	Switch SPDT
Connection:	Spade cable shoes 6.3 × 0.8 mm, 189157: although 4.8 × 0.5 mm
Switch material:	Silver
Mechanical life:	30 × 10 ⁵ functions at max. contact load
Temp. range:	-55°C* to +85°C
Dimensions:	See drawings



ENGLISH

Specifications:

Actuator Type	Lever
Terminal Type	Solder
Contact Current Rating	4 A @ 28 V dc
Contact Configuration	SPDT
Operating Force	0.275 N
Minimum Operating Temperature	-54°C
Maximum Operating Temperature	+121°C
Contact Material	Silver Plated
Mechanical Life	10 ⁷ Operations
Release Force	0.141N
Operating Temperature Range	-54 → +121°C