


## Datasheet

### SP-CO Lever Microswitch, 0.03 A@ 250 V dc, 0.25 A@ 250 V dc, 15 A@ 440 V ac, 4 A@ 440 V ac

RS Stock 797-2570



### Dimensions: (mm)



- Single pole changeover, snap acting switches
- Fine silver contacts
- Beryllium copper trident spring operating mechanism
- The lever actuator in free position keep the plunger depressed which is released when the lever is pressed downwards
- Easy wire-up screw and cup-washer terminals characterised by extended creepage distance between terminals
- Conform to IEC 1058-2 Standard

**ENGLISH**

## Specifications

Characteristics	
Actuating force	225gms (max)
Release force	29 gms (min)
Pre – travel	7.2 mm (max)
Over – travel	5.6mm
Movement differential	0.76mm (max)
Salient features	Reverse acting stainless steel plain lever of 56mm. radius

Technical Data	
Contact resistance	1 milliohms (max)
Insulation resistance	1000 megaohms (min)
Voltage proof	1 KV AC for one minute
Terminals	M 3.5 screw with cup washer
Electrical life	50,000 operations
Mechanical life	1 million operations

Electrical Rating	
Load	Rating
AC	15A at 125V or 15A at 250V or 15A at 440V
AC	15A at 125V or 15A at 250V or 4A at 440V
DC	0.5 A at 125V or 0.25 A at 250V
DC	0.05 A at 125V or 0.03 A at 250V