

4-15W AC-DC Board Mount Power Supplies

Features

- ◆ Low profile
- ◆ Smaller footprint
- ◆ PC board Mountable
- ◆ Low Cost
- ◆ UL Class II Approved
- ◆ Wide input range
- ◆ No external components needed



Key Market Segments & Applications



Specifications		KPSA-5	KPSA-10	KPSA-15
Input Voltage range	-	85 - 264VAC (47 - 63Hz) or 110 - 370VDC*		
Inrush Current	A	30A at 240VAC, cold start at 25°C		
Input Current (115/230VAC)	A	0.13 / 0.07	0.27 / 0.13	0.4 / 0.2
Leakage Current	mA	0.25mA maximum		
Temperature Coefficient	-	±0.05%/°C		
Voltage Accuracy	-	±1%		
Minimum Load	A	None		
Load Regulation	-	±1% (10% to 100% load)		
Line Regulation	-	±0.5% (100-240VAC line change)		
Ripple & Noise (1)	mV	1% or 50mV whichever is greater		
Short Circuit Protection	-	Continuous - hiccup mode		
Overvoltage Protection	V	130-150%, Zener clamp		
Efficiency (typical)	%	72%	75%	75%
Hold Up Time (Typ@115VAC input)	ms	14ms at full load		
LED Indicator	-	Green LED = OK		
Operating Temperature (2)	°C	Convection cooling: 0 to +70°C, derating linearly to 25% load from 40 to 70°C		
Storage Temperature	°C	-20 to +85°C		
Humidity (non condensing)	-	10 - 95% RH		
Cooling	-	Convection or forced air		
Withstand Voltage	-	Input to Output 3kVAC		
Vibration (non operating)	-	23.52m/s ² (10 - 55Hz: constant sweep 1 min X, Y, Z for 1 hour)		
Shock	-	< 196.1 m/s ² (20G)		
Safety Agency Approvals	-	IEC/UL/CSA/EN62368-1, 60950-1, Class II, CE Mark		
Conducted & Radiated EMI	-	EN55022-B, FCC Class B		
Immunity	-	EN61000-4 -2, -3, -4, -5, -6		
Weight (Typ)	g(oz)	29g (1oz)	60g (2oz)	80g (2.8oz)
Size (WxLxH; H above pcb)	in.	1.28 x 2.17 x 0.83	1.55 x 2.40 x 0.9	1.77 x 2.75 x 0.79
Warranty	yr	One Year		

*Safety certified for AC input only.


Notes:

- (1) Measured with 0.1uF ceramic & 10uF electrolytic at 20MHz BW
- (2) 20CFM forced air ratings:
 - KPSA5: 0 - 70°C full load
 - KPSA10: 0 - 70°C full load (3.3V & 5V models derate linearly to 80% load from 50 to 70°C)
 - KPSA15: 0 - 70°C derate linearly to 80% load from 50 to 70°C


Model Selector (other voltages available)

Model	Output Voltage (V)	Maximum Output (A)	Output Pwr (W)
KPSA5-3R3	3.3	1.25	4.1
KPSA5-5	5	1.0	5.0
KPSA5-12	12	0.42	5.0
KPSA5-15	15	0.33	5.0
KPSA5-24	24	0.23	5.5
KPSA10-3R3	3.3	2.5	8.3
KPSA10-5	5	2.0	10.0
KPSA10-12	12	0.84	10.1
KPSA10-15	15	0.67	10.1
KPSA10-24	24	0.42	10.1
KPSA15-3R3	3.3	3.0	9.9
KPSA15-5	5	3.0	15.0
KPSA15-12	12	1.25	15.0
KPSA15-15	15	1.0	15.0
KPSA15-24	24	0.63	15.1


KPSA10 Outline Drawing



KPSA5 Outline Drawing



KPSA15 Outline Drawing



For Additional Information, please visit
<https://product.tdk.com/en/power/>

