

Product designation	Modular LCD multimeters.		
Product type designation	expandable		
Type	DMG300		
DIN rail module number	Three-phase + neutral		
	4		
<b>Auxiliary supply Us</b>			
Auxiliary rated supply voltage AC	VAC	100...240	
Auxiliary rated supply voltage DC	VDC	110...250	
Auxiliary operating voltage range			
AC	min	VAC	85
	Max	VAC	264
DC	min	VDC	93.5
	Max	VDC	300
Operational frequency	min	Hz	45
	max	Hz	66
Power consumption	Max	VA	3.2
Power dissipation Max		W	1.3
<b>Measuring voltage inputs</b>			
Rated voltage (Ue)	phase-phase	VAC	690
	phase-neutral	VAC	400
Operating voltage range	phase-phase	VAC	20...830
	phase-neutral	VAC	10...480
Voltage inputs operational frequency	min	Hz	45
	max	Hz	66
Voltage inputs measurement method	True RMS		
Connection method	Single. two. three-phase with or without neutral. balanced three-phase systems		
<b>Current inputs</b>			
Rated current (Ie)	A	1 / 5	
Measurement range	0.01...1.2 / 0.01...6		
Measurement method	TRMS		
Overload capacity	+20% Ie through external CT with 5A secondary		
Overload peak	A	50A for 1s	
<b>Accuracy</b>			
Measurement conditions (T +23°C ±1°C / Rel. Humidity 45 ±15% R.H.)	VLN voltage	±0.5%	
	VLL voltage	±0.5%	
	current	±0.5%	
	frequency	±0.05%	

active power	±1%
active energy	Class 1 (IEC/EN 62053-21)
reactive energy	Class 2 (IEC/EN 62053-23)

### Insulations

Rated insulation voltage $U_i$ IEC/EN	V	690
Rated impulse withstand voltage $U_{imp}$	kV	9.5
Operating frequency withstand voltage	kV	5.2

### Mechanical features

Housing type	Polyamide		
Terminals type	Fixed		
Conductor cross section			
	min	mm <sup>2</sup>	0.2
	Max	mm <sup>2</sup>	4
	min	AWG	24
	Max	AWG	12

### Tightening torque (Max)

	Nm	0.8
	lbin	7
Fixing	DIN rail	
Weight	g	320

### Ambient conditions

#### Temperature

##### Operating temperature

min	°C	-20
max	°C	+60

##### Storage temperature

min	°C	-30
max	°C	+80

Relative humidity	%	<90
Maximum Pollution degree	2	
Protection degree	IP30	

### Dimensions

### Wiring diagrams

### Certifications and compliance

#### Compliance

CSA C22.2 n°14  
IEC/EN 61000-6-2  
IEC/EN 61000-6-4  
IEC/EN 61010-1  
UL508

#### Certificates

cULus  
EAC  
GOST  
RCM

### ETIM classification

ETIM 8.0

EC002301 -  
Multifunction  
measuring  
instrument