

Energy storage - UPS-BAT/PB/24DC/4AH - 1274117

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Energy storage, VRLA-AGM, 24 V DC, 4 Ah, automatic detection and communication with QUINT UPS-IQ

Product Description


For continuous monitoring and intelligent management, there is constant communication with the QUINT UPS. Thanks to automatic detection of the energy storage, and tool-free switching during operation, quick installation is possible. The QUINT UPS with IQ technology energy storage leaves the warehouse fully charged.

Your advantages

- ✓ Maximum buffer times
- ✓ Lead AGM (Absorbent Glass Mat) technology



Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 466619
GTIN	4063151466619
Weight per Piece (excluding packing)	4,260.000 g
Custom tariff number	85072080
Country of origin	China

Technical data

Dimensions

Width	85 mm
Height	191 mm
Depth	110 mm
Installation distance right/left	0 mm / 0 mm

Energy storage - UPS-BAT/PB/24DC/4AH - 1274117

Technical data

Dimensions

Installation distance top/bottom	50 mm / 50 mm
----------------------------------	---------------

Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C ... 40 °C
Ambient temperature (charge)	0 °C ... 40 °C
Ambient temperature (discharge)	-20 °C ... 50 °C
Max. permissible relative humidity (operation)	≤ 95 %
Degree of pollution	2

General

Protection class	III
Degree of protection	IP20
Degree of pollution	2
Weight	3.3 kg
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
Connection in parallel	yes
	max. 5
Connection in series	No
Battery type	BB Battery HR4.2-12FR
Battery technology	VRLA-AGM
IQ-Technology	yes
Temperature sensor	yes
Latest startup date (battery only)	6 Months (0 °C ... 20 °C)
Latest startup (battery only) - range	3 Months ... 6 Months (20 °C ... 30 °C)
	1 Months ... 3 Months (30 °C ... 40 °C)
Accumulator module service life (according to Eurobat)	6 (20 °C)
Storage medium	VRLA-AGM
Size designation	Block

Input data

Input voltage	24 V DC (SELV)
Nominal capacity	4 Ah
Charge current	1.2 A
End-of-charge voltage	27.6 V DC (20 °C)

Output voltage	24 V DC
----------------	---------

Energy storage - UPS-BAT/PB/24DC/4AH - 1274117

Technical data

Output current I_{max}	25 A
Output fuse	1x 25 A
Buffer time	4.5 min. (20 A)
	3 min. (25 A)

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 8
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Pictogram



Classifications

eCl@ss

eCl@ss 11.0	27050403
eCl@ss 9.0	27050403

ETIM

ETIM 7.0	EC000357
----------	----------

Energy storage - UPS-BAT/PB/24DC/4AH - 1274117

Approvals

Approvals

Approvals

cULus Listed / EAC / DNV GL / cULus Listed / EAC

Ex Approvals

cULus Listed / cULus Listed

Approval details

cULus Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 123528
--------------	--	---	---------------

EAC			RU*DE*01.B.78948/21
-----	--	--	---------------------

DNV GL		https://approvalfinder.dnvgl.com/	TAA0000265
Nominal voltage UN		500 V	
Nominal current IN		41 A	
mm ² /AWG/kcmil		6	

cULus Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 123528
--------------	--	---	---------------

EAC			RU*DE*01.B.78948/21
-----	--	--	---------------------

Accessories

Accessories

Assembly adapter

Energy storage - UPS-BAT/PB/24DC/4AH - 1274117

Accessories

Mounting adapter - QUINT-ADAPTER/4 - 2866857

Assembly adapter for QUINT-BAT/24DC... on 35mm rail



Battery unit

Uninterruptible power supply replacement battery - UPS-BAT-KIT/PB/2X12V/4AH - 1283116



Replacement battery, VRLA-AGM, 2x12 V DC, 4 Ah. Only for 1274117 UPS-BAT/PB/24DC/4AH, 2320267 QUINT-UPS/24DC/24DC/10/3.4AH from V/C 06, 2905908 TRIO-UPS-2G/1AC/1AC/120V/750VA, and 2905909 TRIO-UPS-2G/1AC/1AC/230V/750VA

Fuse

Fuse - FUSE 25A/32V ATOF - 2908366



Fuse, nominal current: 25 A, length: 19.1 mm, width: 5 mm, height: 18.8 mm