

## Product: <u>AX101448</u> ☑



## **GIGABIX CONNECTOR 25-PAIR**

# Product Description

GIGABIX CONNECTOR 25-PAIR

## **Technical Specifications**

## **Product Overview**

| Suitable Applications:             | IBDN System 4800, 3600, 2400, TIA Category 6, ISO Class E, 1000BASE-T |  |
|------------------------------------|---|--|
| Physical Characteristics (Overall) |   |  |
| Insulation                         |   |  |
| Nominal Diameter                   |   |  |
| 0.146 mm                           |   |  |
| Packaging:                         | packaged in carton; Standard pack of 12 units                         |  |
| Weight:                            | 0.11 g  |  |

## Connectors

## Materials

| Description      | Material                         | Туре |
|------------------|----------------------------------|------|
| Front Connection | Copper Allow with Nickel Plating | IDC  |
| Rear Connection  | Copper Allow with Nickel Plating | IDC  |
| Connector Body   | Plastic - UL940V-0               |      |

### **Construction and Dimensions**

## OuterJacket1, Nom Thick Twisted Section: 0.147 mm

## **Electrical Characteristics**

| Dielectric Strength:    | 1,000V RMS @ 60 Hz for 1 minute kV DC |  |
|-------------------------|---------------------------------------|--|
| Current Rating:         | 1.5 A                                 |  |
| Insulation Resistance:  | 100 MOhm*km                           |  |
| Max Contact Resistance: | 1 mOhm                                |  |

## Inductance

```
Nominal Inductance
```

```
0.145 µH/m
```

### Mated Connection

| Frequency (MHz | Max. Insertion Loss TIA* (dB) | Min. NEXT TIA* (dB) | Min. FEXT TIA* (dB) | Min. FEXT Belden** (dB) | Min. Return Loss TIA* (dB) |
|----------------|-------------------------------|---------------------|---------------------|-------------------------|----------------------------|
| 100            | 0.2 dB                        | 54 dB               | 43.1 dB             | 58.8 dB                 | 24 dB                      |

## **Temperature Range**

| Installation Temp Range: | -10°C To +60°C |
|--------------------------|----------------|
| Storage Temp Range:      | -40°C To +70°C |
| Operating Temp Range:    | -10°C To +60°C |

#### **Mechanical Characteristics**

| Footprint/Type:     | GigaBIX                        |
|---------------------|--------------------------------|
| Tool Compatibility: | BIX Connecting Tool (A0270165) |

### **Termination Interface**

| Termination | Connection               | Durabilities     |
|-------------|--------------------------|------------------|
| Front       | Gas Tight IDC Connection | 200 terminations |
| Rear        | Gas Tight IDC Connection | 200 terminations |

### Dimensions (WxHxD)

Height Depth Width 6.63 0.31 1.28

## **Standards**

| ISO/IEC Compliance:                   | ISO/IEC 11801:2002              |  |
|---------------------------------------|---------------------------------|--|
| Data Category:                        | Category 6                      |  |
| TIA/EIA Compliance:                   | ANSI/TIA/EIA 568 C.2 Category 6 |  |
| Third Party Performance Verification: | ETL - Verified Category 6       |  |

#### **Applicable Environmental and Other Programs**

| Environmental Space:     | Indoor                         |  |
|--------------------------|--------------------------------|--|
| EU Directive Compliance: | EU Directive 2002/95/EC (RoHS) |  |
|                          |                                |  |

#### Suitability

| Suitability - Indoor: | Yes |
|-----------------------|-----|

#### Flammability, LS0H, Toxicity Testing

ACA,UL 1863 and CSA-C22.2

#### **Related Part Numbers**

Related Parts:

Compatible with GigaBIX patch cord, GigaBIX termination kit, GigaBIX rack mount panel, designation strips, wire guard

#### Variants

Item # Colo AX101448 White 611589002783

#### **Product Notes**

Notes: For proper installation refer to Installation Guide PX101813 (French) or PX101814 (English) included with the product or visit our web site at http://www.belden.com History Update and Revision: Revision Number: 0.89 Revision Date: 12-15-2021

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.