

# Locking Devices



## 30 Amp Plugs, Connectors Flanged Devices and Receptacles

30A 125V, 250V, 277V AC, 480V AC and 600V AC Locking Devices,  
2-Pole 3-Wire Grounding Inches (mm)

**TECH·SPEC®**




Rating	Cord Diameter	Description	Tripple Gripper		Flanged Devices Equipment Base with Nylon White Cup		Weather Protective Power Inlets Die Cast Aluminum Plate*	Single Nylon Receptacle, All Black
			Nylon Plug	Nylon Connector	Male	Female		
NEMA L5-30, 30A 125V	.300"-.950" (7.6-24.1)	Black/White	<b>70530NP</b>	<b>70530NC</b>	<b>70530MB</b>	<b>70530ER</b>	<b>70530MBWP</b>	—
		All Black	<b>70530NPB</b>	<b>70530NCB</b>	—	—	—	<b>70530FR</b>
		Corrosion-Resistant Yellow/White	<b>70530NPCR</b>	<b>70530NCCR</b>	—	—	—	<b>70530FRCR</b>
NEMA L6-30, 30A 250V	.300"-.950" (7.6-24.1)	Black/White	<b>70630NP</b>	<b>70630NC</b>	<b>70630MB</b>	<b>70630ER</b>	<b>70630MBWP</b>	—
		All Black	<b>70630NPB</b>	<b>70630NCB</b>	—	—	—	<b>70630FR</b>
		Corrosion-Resistant Yellow/White	<b>70630NPCR</b>	<b>70630NCCR</b>	—	—	—	—
NEMA L7-30, 30A 277V AC	.300"-.950" (7.6-24.1)	Black/White	<b>70730NP</b>	<b>70730NC</b>	<b>70730MB</b>	<b>70730ER</b>	—	<b>70730FR</b>
		Black/White	<b>70830NP</b>	<b>70830NC</b>	<b>70830MB</b>	<b>70830ER</b>	—	<b>70830FR</b>
		Black/White	<b>70930NP</b>	<b>70930NC</b>	<b>70930MB</b>	<b>70930ER</b>	—	<b>70930FR</b>
NEMA L8-30, 30A 480V AC	.300"-.950" (7.6-24.1)	Black/White	<b>70830NP</b>	<b>70830NC</b>	<b>70830MB</b>	<b>70830ER</b>	—	<b>70830FR</b>
		Black/White	<b>70930NP</b>	<b>70930NC</b>	<b>70930MB</b>	<b>70930ER</b>	—	<b>70930FR</b>
		Black/White	<b>70930NP</b>	<b>70930NC</b>	<b>70930MB</b>	<b>70930ER</b>	—	<b>70930FR</b>
NEMA L9-30, 30A 600V AC	.300"-.950" (7.6-24.1)	Black/White	<b>70930NP</b>	<b>70930NC</b>	<b>70930MB</b>	<b>70930ER</b>	—	<b>70930FR</b>
		Black/White	<b>70930NP</b>	<b>70930NC</b>	<b>70930MB</b>	<b>70930ER</b>	—	<b>70930FR</b>
		Black/White	<b>70930NP</b>	<b>70930NC</b>	<b>70930MB</b>	<b>70930ER</b>	—	<b>70930FR</b>

Note: \*Supplied with gaskets, mounting screws and spring-loaded, self-closing lift cover.  
See Section D for more information on isolated ground devices and Section J for more information on corrosion-resistant devices.  
See page H-20 for weather protective boots for 20 amp nylon locking plugs.

## Product Dimensions Inches (mm)

Plug	
A	2.86" (72.4)
B	1.89" (48.0)
C	2.13" (54.1)
Connector	
A	3.90" (99.1)
B	1.89" (48.0)
C	2.13" (54.1)



	Receptacle Single	Flanged Devices Male/Female
A	3.28" (83.3)	2.88" (73.2)
B	2.38" (60.5)	120°
C	1.56" (39.6)	2.50" (63.5)
D	1.70" (43.2)	2.02" (51.3)
E	2.67" (67.8)	2.05" (52.1)
F	1.24" (31.5)	(3) 0.19" (4.8)

Note: See page S-8 for horsepower ratings.

