



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Main Input Voltage	120 V
Plug standard	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Black
Height	1.18 in (3 cm)
Width	3.03 in (7.7 cm)
Depth	12.09 in (30.7 cm)
Net Weight	1.48 lb(US) (0.67 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	12
Outlet standard	NEMA 5-15R

Conformance

Product certifications	MET USA MET Canada
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	56 KA common mode 28 kA normal mode
Surge energy rating	2160 J

Ordering and shipping details

GTIN	8411314066804
Package weight(Lbs)	1.70 lb(US) (0.77 kg)

Packing Units

Package 1 Height	1.89 in (4.8 cm)
Package 1 width	5.71 in (14.5 cm)
Package 1 Length	13.19 in (33.5 cm)
SCC14	10731304335945
Number of Units in Package 2	6
Package 2 Weight	11.04 lb(US) (5.01 kg)
Package 2 Height	12.6 in (320.04 mm)
Package 2 width	6.3 in (160.02 mm)
Package 2 Length	13.78 in (350.01 mm)
Number of Units in Package 3	324

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	Lifetime
----------	----------