

# 15A, 125V, 2 Pole, 3 Wire Grounding Extra Heavy Duty SNAPConnect® Receptacles

# HUBBELL

### Features

- Audible SNAP, indicates solid connection
- Reduces installation time
- Fully insulated design

### Ordering Information

|                                     |              |              |                |
|-------------------------------------|--------------|--------------|----------------|
| Description                         | Device Color | UPC          | Catalog Number |
| Specification grade, finder groove. | Gray         | 783585247823 | SNAP5262GYA    |

### Listings

UL Listed to UL498 File No. E2186  
Certified to CSA, C22.2, No. 42 File 285  
Fed. Spec. W-C-596  
NEMA® WD-6 Compliant

### Specifications

|                            |                   |
|----------------------------|-------------------|
| Face                       | Nylon             |
| Base                       | PBT               |
| Contacts                   | Brass             |
| Mounting Strap             | Galvanized steel  |
| Auto Self-grounding Staple | Stainless steel   |
| Mounting Screws            | Zinc plated steel |

### Performance

|                        |                                                                     |
|------------------------|---------------------------------------------------------------------|
| <b>Electrical</b>      |                                                                     |
| Current Interrupting   | Receptacle certified for current interrupting at full rated current |
| Dielectric Voltage     | Withstands 2,000V minimum                                           |
| <b>Mechanical</b>      |                                                                     |
| Product Identification | Ratings are a permanent part of the device                          |
| <b>Environmental</b>   |                                                                     |
| Flammability           | UL 94V-2                                                            |
| Operating Temperature  | Maximum continuous 75°C; minimum -40°C (without impact)             |



### Accessories

Wallplate or Weatherproof Cover Duplex Opening

### Resources

[eCatalog](#)

