

Watertight Devices

GFCI Protected FD Box

240V, Up to 30A, Auto Reset

HUBBELL

Features

- UL Enclosure type 4X
- For use with Watertight Receptacles
- Components are UL and CSA Listed

Ordering Information

Description	Catalog Number	UPC
Watertight FD Box, 120V, Up to 30A, GFCI module	HBLWTGF240	783585511016

Listings

UL Enclosure Type 4X
For wet and damp locations
Components UL & CSA listed


Specifications

FD Box Enclosure	Yellow PBT
Mounting Plate	Stainless Steel
GFCI Module	Class A GFCI
Total Weight	4.4 lbs
PolyTuff Liquidtight Fitting	Nylon
PolyTuff Liquidtight Fitting	3/4" NPT
PolyTuff Liquidtight Conduit	Co-extruded rigid and flexible PVC

Performance

Electrical	
Amperage	Up to 30A
Voltage	240V

Environmental	
FD Box Flammability	UL94 V-0



Accessories

Watertight Receptacles	HBL60W49, HBL60W49D, HBL60W48, HBL60W48D, HBL65W49, HBL65W49D, HBL67W48, HBL69W48
------------------------	---

Online Resources

Customer Use Drawing
eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

