



APPROVALS



Available upon request

Picture is a representation of actual product

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H
kg/mm								
3-7	130.0	22.0	25.0	M6 x 1.0	25.4	15.0	106.0	12.0
10-30	130.0	22.0	25.0	M6 x 1.0	30.0	15.0	106.0	12.0
35	130.0	22.0	25.0	M6 x 1.0	40.0	15.0	106.0	12.0

Order Information

Load Rating	Part #	Est. Weight	Price
1.5 ft Cables			
3 kg	41135	2 lb	Consult
5 kg	41136	2 lb	Consult
7 kg	41137	2 lb	Consult
10 kg	41138	2 lb	Consult
15 kg	41139	2 lb	Consult
20 kg	41140	2 lb	Consult
30 kg	41141	2 lb	Consult
35 kg	41142	2 lb	Consult
10 ft Cables			
3 kg	132269	2 lb	Consult
5 kg	132270	2 lb	Consult
7 kg	132271	2 lb	Consult
10 kg	132272	2 lb	Consult
15 kg	132273	2 lb	Consult
20 kg	132274	2 lb	Consult
30 kg	132275	2 lb	Consult
35 kg	132276	2 lb	Consult
1.5 ft Cables			
10 kg	150770	2 lb	Consult
15 kg	150771	2 lb	Consult
20 kg	150772	2 lb	Consult
30 kg	150773	2 lb	Consult

Interchangeable Products

RICE LAKE WEIGHING SYSTEMS	
RL1521A.....	page 191
VPG® CELTRON	
LPS.....	page 234
VPG® BLH	
C2G1.....	—
NMB®	
C2G1.....	—

Specifications

- Full Scale Output:**
2.0 mV/V
- Output Resistance:**
350 (± 3) ohm
- Input Resistance:**
415 (± 15) ohm
- Material/Finish:**
Anodized aluminum
- Temperature:**
Compensated range
14°F to 104°F (-10°C to 40°C)
Operating range
0° F to 150° F (-18° C to 65° C)
- Seal Type:**
Environmentally sealed, IP66
- Safe Overload:**
150% full scale
- Rated Excitation:**
5- 10 VDC (15 V maximum)
- Combined Error:**
0.02% full scale
- Insulation Resistance:**
2,000 megohms
- Cable Length:**
10 ft
1.5 ft
- Cable Diameter:**
0.140 in PVC jacket
- Cable Color Code:**
Green +Excitation
Black -Excitation
Red +Signal
White -Signal
- Platform Size:**
13.78 in x 13.78 in
- Warranty:**
One-year limited warranty
- Approvals:**
cFMus
NTEP
OIML
Ex (Available upon request)

