"X" DIM. ASS'Y P/N CARA168804SP03990 3 FT. 3 1/2 IN. ± 2 IN. [1M ±50.8mm] CARA168804SP07990 6 FT. 7 IN. ± 2 IN. [2M ±50.8mm] FINISHED CABLE ASSEMBLY TO BE COILED OVERMOLD BOOT MATERIAL: UV PBT, BLACK 16 FT. 5 IN. ± 4 IN. [5M ±101.6mm] CARA168804SP19790 ELECTRICAL TEST: 100% CONTINUITY
ALL DIMENSIONS ARE REFERENCE ONLY CARA168804SP39490 32 FT. 9 3/4 IN. ± 8 IN. [10M ±203.2mm] CARA168804SPXXX90 EXCEPT WHEN NOTED WITH TOLERANCE CABLE LENGTH IN "INCHES" "X" DIM. 1.029 IN. CUSTOMER PRINT [26.1mm] -CUT BLUNT 1.100 IN. [27.9mm] RIGHT ANGLE OVERMOLDED CABLE CONNECTOR, FEMALE $\Sigma\Sigma\Sigma\Sigma$ (4)-#22 AWG CONDUCTORS JACKET: PVC, BLACK MAT'L: UV PBT, BLACK
(4) #22 SOCKET CONTACTS
MAT'L: GOLD PLATED 0.195 O.D. REF. 300 V **COPPER ALLOY** COUPLING RING MAT'L: UV PBT, BLACK O-RING MAT'L: SILICONE, RED ARROW AND KEY ALIGNED CARA168804SPXXX90 MASTER KEYWAY MAT'L: STAINLESS STEEL END "A" FACE VIEW **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION. ΑN 06-08-21 DRAWING CREATED PER DOR 21-109360DS REV. INIT. DATE DESCRIPTION 06-08-21 AN CHECKED BY: APPROVED BY: 601 E. WILDWOOD VILLA PARK, IL 60181 DATE: _ CABLE ASSEMBLY WIRE COLOR CODE, END "A" (4) #22 SOCKET CONTACTS INSTA-CLICK™ MICRO-CON-X STANDARD PRODUCT POS. 1 POS. 2 POS. 3 POS. 4 SCALE SIZE NTS B SHEET 1 OF 1 **Rohs Compliant** BLU BRN DIMENSIONS IN BRACKETS [] ARE METRIC PART NUMBER: CARA168804SPXXX90 = CRITICAL CHARACTERISTIC FLAG PER SPEC, XXXX