

Molex's range of pre-crimped leads offers a simple, cost-effective solution for prototyping, pre-production and mass production requirements. These leads are offered in female-to-female and male-to-male configurations in lengths of 75.00 to 600.00mm



C-Grid III

CLIK-Mate



DuraClik



iGrid



KK



LINK 250



LINK 396



Mega-Fit




MicroClasp



Micro-Fit 3.0



Micro-Lock Plus



Micro-Lock Plus 2.0



Milli-Grid



Mini-Fit



Mini-Fit Sr.




Mini-Lock



Mizu-P25



MLX



MultiCat




MX150



Nano-Fit



PicoBlade



Pico-Clasp



Pico-EZmate



Pico-Lock



Pico-SPOX



Sabre




Sherlock



SL



Solderless Ring



Squba 1.80mm



Squba 3.60mm



Standard .062"



Standard .093"



Ultra-Fit

| Product Family      | Series Number   | Length (mm)             | Connector A  | Connector B     | Wire Size (AWG) | Wire/Cable Type   |
|---------------------|---|-------------------------|--------------|-----------------|-----------------|-------------------|
| C-Grid              | 79758   | 150, 300                | Female       | Female          | 22              | UL 1061           |
| CLIK-Mate           | 79758, 215710,<br>215711  | 75, 150, 225, 300, 450  | Female, Male | Female, Male    | 24, 26, 28      | UL 1061, UL 10002 |
| DuraClik            | 79758   | 150, 300                | Female       | Female          | 26              | UL 1061           |
| iGrid               | 217490, 217491  | 75, 150, 225, 300, 450  | Female       | Female          | 22, 24, 26      | UL 10002          |
| KK                  | 79758   | 150, 300                | Female, Male | Female, Male    | 22, 24          | UL 1061, UL 1007  |
| L1NK 396            | 79758   | 150                     | Female       | Female          | 18              | UL 1051           |
| Mega-Fit            | 79758   | 150, 300                | Female       | Female          | 16, 12          | UL 1015           |
| Micro-Clasp         | 79758   | 150, 300                | Female       | Female          | 24              | UL 1007           |
| Micro-Fit 3.0       | 79758, 214760,<br>214761, 214762,<br>214763                             | 150, 300, 600           | Female, Male | Female, Male, - | 18, 20          | UL 1061, UL10002  |
| Micro-Lock Plus     | 79758   | 150, 300                | Female       | Female          | 26              | UL 1061           |
| Micro-Lock Plus 2.0 | 217500<br>217501  | 75, 150, 225, 300, 450  | Female       | Female, Strip   | 22, 24, 26      | UL 10002          |
| Milli-Grid          | 79758   | 150, 300                | Female       | Female          | 24              | UL 1061           |
| Mini-Fit            | 79758, 215340,<br>215341, 215342,<br>215343                             | 75, 150, 225, 300, 450  | Female, Male | Female, Male    | 16, 18, 20      | UL 1015, UL 1061  |
| Mini-Fit Sr.        | 217480, 217481,<br>217482, 217483                                       | 150, 225, 300, 450      | Female, Male | Female, Male    | 8, 10, 12       | UL 10669          |
| Mini-Lock           | 79758   | 150, 300                | Female       | Female          | 22              | UL 1061           |
| Mizu-P25            | 217840, 217841,<br>217842, 217843,<br>217520, 217521,<br>217522, 217523 | 75, 150, 225, 300, 450, | Female, Male | Female, Male    | 20, 22          | UL10002, FLY-B    |
| MLX                 | 79758   | 150, 300                | Female, Male | Female, Male    | 18              | UL 1015           |
| Multicat            | 79758   | 150, 300                | Female, Male | Female, Male    | 8, 9, 12, 16    | UL 1199           |
| MX150               | 216300, 216301,<br>216302, 216303                                       | 150, 225, 300, 450, 600 | Female, Male | Female, Male    | 14, 16, 18      | TXL               |

### Ordering Information

| Product Family | Series Number                         | Length (mm)            | Connector A  | Connector B  | Wire Size (AWG) | Wire/Cable Type   |
|----------------|---------------------------------------|------------------------|--------------|--------------|-----------------|-------------------|
| Nano-Fit       | 79758                                 | 150, 300               | Female       | Female       | 20              | UL 1061           |
| PicoBlade      | 79758, 214920, 214921, 214922, 214923 | 75, 150, 225, 300, 450 | Female, Male | Female, Male | 26, 28          | UL1061            |
| Pico-Clasp     | 79758                                 | 150, 300               | Female       | Female       | 28              | UL 1571           |
| Pico-EZmate    | 79758                                 | 300                    | Female       | Female       | 28              | UL 1516           |
| Pico-Lock      | 79758                                 | 150, 300               | Female       | Female       | 24, 30          | UL 1061, UL 1571  |
| Pico-SPOX      | 79758                                 | 150, 300               | Female       | Female       | 24              | UL 1061           |
| Sabre          | 79758                                 | 150, 300               | Female, Male | Female, Male | 16              | UL 1015           |
| Sherlock       | 79758                                 | 150, 300               | Female       | Female       | 26              | UL 1061           |
| SL             | 79758                                 | 150                    | Female       | Female       | 22              | UL 1061           |
| Squba 1.80mm   | 217790, 217791, 217792, 217793        | 75, 150, 225, 300, 450 | Female       | Female       | 22, 24          | UL 10002          |
| Squba 3.60mm   | 215345, 215346, 215347, 215348        | 75, 150, 225, 300, 450 | Female, Male | Female, Male | 16, 18, 20      | UL 11028          |
| Standard .062" | 79758                                 | 150, 300               | Female, Male | Female, Male | 22              | UL 1015           |
| Standard .093" | 79758                                 | 150, 300               | Female, Male | Female, Male | 18              | UL 1015           |
| Ultra-Fit      | 79758, 217470, 217471                 | 75, 150, 225, 300, 450 | Female       | Female       | 16, 18, 20      | UL 1061, UL 11028 |

| Product Family           | Series Number | Length (mm) | Stud Size | Wire Termination | Wire Size (AWG) | Wire/Cable Type |
|--------------------------|---------------|-------------|-----------|------------------|-----------------|-----------------|
| Solderless Ring Terminal | 217851        | 150         | 10 (M5)   | Blunt cut        | 16 AWG          | UL 1015         |
|                          |               | 300         |           |                  |                 |                 |
|                          |               | 600         |           |                  |                 |                 |