

PRODUCT-DETAILS

# RB14-250F

## INS NYL FEM-250 DISC 16-14 LEN .91



### General Information

Extended Product Type	RB14-250F
Product ID	7TAI029690R0012
EAN	5414363135166
Catalog Description	INS NYL FEM-250 DISC 16-14 LEN .91
Long Description	Nylon Insulated Female Disconnect, Length .91 Inches, Width .29 Inches, Maximum Insulation .162, Tab Size .250x.032, Wire Range #16-#14, Color Blue, Copper, Tin Plated, 100 Pack

### Ordering

EAN	5414363135166
UPC	786210804255
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

### Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	1.25 in 32 mm
Package Level 1 Height	2.5 in 64 mm
Package Level 1 Depth /	3.5 in

Length	89 mm
Package Level 2 Units	500 piece
Package Level 2 Width	9.6 in 244 mm
Package Level 2 Height	8.8 in 224 mm
Package Level 2 Depth / Length	15.1 in 384 mm
Package Level 3 Units	5000 piece
Package Level 3 Width	9.875 in 251 mm
Package Level 3 Height	12 in 305 mm
Package Level 3 Depth / Length	7.5 in 191 mm

### Additional Information

Brand / Label	Sta-Kon
Color	Blue
Effective Date	19750203
Insulation Material	Nylon/Polyamide
Material	Brass
Product Name	ELECTRICAL TERMINAL
Product Type	Nylon Insulated Female Disconnect
Special Functions	Unique construction of the female disconnect offers long-term dependability. Brazed seam serrated barrel provides maximum tensile strength.
Standards	UL E66716
Surface Finishing	Tin Plated

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	RB14-250F
Instructions and Manuals	RB14-250F

### Classifications

ETIM 6	EC000516 - Round or flat plug/receptacle
ETIM 7	EC000516 - Round or flat plug/receptacle
ETIM 8	EC000516 - Round or flat plug/receptacle
UNSPSC	39121447
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4667 >> Wire terminal disconnect

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

