

PRODUCT-DETAILS

C10-250F

NON-INS FEM .250x.032 DISC 12-10AWG



General Information

Extended Product Type	C10-250F
Product ID	7TAI029700R0014
EAN	5414363148890
Catalog Description	NON-INS FEM .250x.032 DISC 12-10AWG
Long Description	Non-Insulated Female Disconnect, Length .73 Inches, Width .31 Inches, Tab Size .250x.032, Wire Range #12-#10 AWG, Copper, Tin Plated

Ordering

EAN	5414363148890
UPC	786210803524
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	1.1 in 28 mm
Package Level 1 Height	3 in 76 mm
Package Level 1 Depth / Length	2.09 in 53 mm

Package Level 2 Units	250 piece
Package Level 2 Width	8.9 in 226 mm
Package Level 2 Height	7.3 in 185 mm
Package Level 2 Depth / Length	10.7 in 272 mm
Package Level 3 Units	2500 piece
Package Level 3 Width	7.3 in 185 mm
Package Level 3 Height	8.89 in 226 mm
Package Level 3 Depth / Length	10.6 in 269 mm

Additional Information

Brand / Label	Sta-Kon
Color	Metallic
Effective Date	19690529
Insulation Material	None
Material	Brass
Product Name	ELECTRICAL TERMINAL
Product Type	Non-Insulated Female Disconnect
Special Functions	Unique construction of the female disconnect offers long-term dependability. Brazed seam serrated barrel provides maximum tensile strength.
Standards	UL E66716
Surface Finishing	Tin Plated

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	C10-250F
Instructions and Manuals	C10-250F

Classifications

ETIM 6	EC000516 - Round or flat plug/receptacle
ETIM 7	EC000516 - Round or flat plug/receptacle
ETIM 8	EC000516 - Round or flat plug/receptacle
UNSPSC	39121447
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4667 >> Wire terminal disconnect

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

