


FAS 16 mm FLATPROP EQI

Pressure compensated proportional valve



- > 2/2 NC pressure compensated proportional valve
- > High precision
- > Increased flow - 120 l/min of Air at 2 bar
- > Flat plunger and spring for frictionless operation
- > Highly repeatable with over 100 million cycles



Technical features

Medium:

Air, oxygen or neutral gases

Orifice:

4,5 mm

Filtration:

A filtration of 20 micrometer is required before the inlet

Operation:

2-way valve Normally closed

Hysteresis:

See diagrams on page 2

Operating pressure:

0 ... 7 bar (0 ... 101 psi)

Back pressure:

Maximum 10% of inlet pressure

Mounting:

Cartridge, manifold

Size:

16 mm

Life expectancy:

≥ 100 Mio. cycles (with triangular signal)

Internal leakage:

< 10-2 mbar l/s (≈0,6 ml/min)
0 ... p_{max}

External leakage:

< 10-2 mbar l/s (≈0,6 ml/min)
p = 9,5 bar

Weight:

< 50 g (0,11 lbs)

Ambient/media temperature:

+10 ... +50°C (+50 ... +122°F)

Materials:

Body: Stainless steel only or stainless steel/brass

PEEK (only when mounted on sub base)

Seal: FPM, NBR, EPDM

Manifolds

Contact your local fluid control specialist for information about our manifolding capabilities which include laminated polymer manifolds.


Electrical details

Voltage/frequency	See Technical data – standard coils
Power consumption	2,5 W nominal at T=20°C
Insulation class	F (155°C)
Electrical insulation	1000 V a.c.
Protection degree	IP51
Duty cycle	100%
Electrical connection	300 mm A WG24 flying leads

Following options on request

Specific coils
Wider temperature range
Higher acceptable back pressure
OEM specification

Technical data – standard models

Symbol	Voltage (V d.c.)	Current (mA)	Resistance (Ω)	Body Material	Seal Material	Model
	6	417	14,4	Stainless steel/brass	FPM	12-216C-04521+EQIFIL+BEK
	9,5	264	36	Stainless steel/brass	FPM	12-216C-04521+EQIFIL+BEH
	12	211	57	Stainless steel/brass	FPM	12-216C-04521+EQIFIL+BED
	18	138	130	Stainless steel/brass	FPM	12-216C-04521+EQIFIL+BDZ
	24	104	230	Stainless steel/brass	FPM	12-216C-04521+EQIFIL+BDU
	6	417	14,4	Stainless steel/brass	NBR	12-216C-04520+EQIFIL+BEK
	9,5	264	36	Stainless steel/brass	NBR	12-216C-04520+EQIFIL+BEH
	12	211	57	Stainless steel/brass	NBR	12-216C-04520+EQIFIL+BED
	18	138	130	Stainless steel/brass	NBR	12-216C-04520+EQIFIL+BDZ
	24	104	230	Stainless steel/brass	NBR	12-216C-04520+EQIFIL+BDU


Technical data – standard coils

Valve orifice (mm)	Coil resistance at 20°C (+68°F) \pm 3% [R20] (Ω)	Current for maximum flow [nominal] (mA)	Voltage +20°C (+68°F) [nominal] (V)	Power +20°C (+68°F) [nominal] (W)	Max. required voltage for max flow *1) (V)
4,5	14,4	417	6	2,5	9
	36	264	9,5	2,5	14
	57	211	12	2,5	18
	130	138	18	2,5	27
	230	104	24	2,5	36


*1) Please refer to instruction K12M.0001 for recommendation on drive signals

Additional information

Typical flows vs. supply pressure Air, 20°C, without back pressure



Typical hysteresis curves Air, 20°C, without back pressure



Note:

Flow vs. supply pressure curves are for informative purposes only and shall be used only for the pre-selection of the orifice size. Preliminary testing is recommended to take into account all application specific requirements and to select the most adequate orifice. For further information contact your local fluidic specialist.

Accessories

Manifold for cartridge version with G1/4 ports in aluminium



Page 3

S120.0152

