



Catalog Number: W62-1
Product ID: 7TAA267150R0015
UPC Number: 78378633200
Status: A



Actual

Aluminum Service Entrance Wedge Clamp and Slider for Wire Range: 2-6 ACSR, 2-6 AAAC, 1 Str.-6 Sol. , Color Code Orange

- Drop Wire may be Cut to Exact Length for Adjustments in Drop Wire Sag
- Can be Attached to Bare Neutral at any Point in the Span
- Flexible and Rigid Aluminum Bails Grip ACSR, AAC and AAAC Conductors
- Rigid Stainless Steel Bail Grips Copper Neutral Conductors



Actual

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Type	Aluminum Service Wedge Clamp
Special Features	Drop wire may be cut to exact length for adjustments in drop wire sag. Can be attached to bare neutral at any point in the span. Flexible and rigid bails grip ACSR, AAC and AAAC Conductors.
Application	Dead-End Self-supporting Drop Wire
Size	Length 12-1/2 in X Depth 2-3/8 in
Conductor Range	#2 to #6 ACSR AWG ; #2 to #6 AAAC AWG ; #1 STR AL AWG ; #6 SOL AL AWG
Number Of Conductors	1
Material	Aluminum
Finish	Bare
Voltage Rating	35 kV
Insulation	None
Mounting	Yes
Connection	Tension
Environmental Conditions	All Seasons / Conditions



Actual

Packaging

Outer Quantity	100
Outer Dimensions (inches)	13.75x8.75x8.75
Weight Uom	14.63 lbs. per 100

Documents / Support Tools

Catalog	Available on Website
---------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com