




UPC Code : 078477819401

Country Of Origin : Please Contact Customer Service.

RoHS Compliant : Yes



Available Colors :





lvory

White

16262

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Brown

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings At Rated Voltage : 1/2 HP

Electrical Specifications

Amperage: 15 A

Current Limiting : Full Rated Current Dielectric Voltage : Withstands 2000V per UL498

Grounding : Self-Grounding **Pole :** 2

Temperature Rise : Max 30C at 250 cycles OL at 200 pct rated current Voltage : 125 VAC Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94 Operating Temperature : -40°C to 60°C

Material Specifications

Body Material : Thermoplastic Nylon Clamp Nuts : Zinc-Plated Steel Color : Brown Face Material : Thermoplastic Nylon Ground Clips : Brass-Plated Grounding Screw : Brass 8-32 Line Contacts : Brass Triple-Wipe .031 Thick Strap Material : Zinc-Plated Steel Terminal Screws : Brass 10-32

Mechanical Specifications **Product ID** : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-Ibs Terminal Accom. : 14-10 AWG Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Back or Side Wire

Product Features

Brand : Decora Plus


Color : Brown Device Type : Duplex Receptacle Outlet

Feature 4 : Smooth Face

Grade : Heavy-Duty Industrial Specification Grade NEMA : 5-15R

Standards and Certifications ANSI : C-73 CSA C22.2 No. 42 : File 152105 NEMA : WD-6 NOM : 057 UL498 : File E13399 Warranty : 10-Year Limited

Wiring Diagram



⁵⁻¹⁵R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

