



16342

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Brown

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current Dielectric Voltage : Withstands 3000V per UL498 Grounding : Self-Grounding

Pole: 2

Temperature Rise : Max 30C temperature rise at full rated current Voltage : 125 VAC Wire : 3

Environmental Specifications Flammability : Rated V-2 per UL 94

Operating Temperature : -40°C to 60°C

Material Specifications

Body Material : PBT Polyester Blend Clamp Nuts : Steel

Color : Brown

Face Material : PBT Polyester Blend Ground Clips : Brass Grounding Screw : #8 Hex Head,

Triple-Drive Brass

Patents*

CA2483480 MX257790 MX321216 Line Contacts : .030" Brass Strap Material : Steel (Galvanized G60) Terminal Screws : #8 Triple Drive Brass

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs Terminal Accom. : 14-10 AWG Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Side Wire

Product Features

Brand : Decora Plus Color : Brown

Device Type : Duplex Receptacle Outlet Feature 4 : Smooth Face Grade : Commercial Specification Grade

Grounding : Self-Grounding NEMA : 5-20R

Standards and Certifications ANSI : C-73 NEMA : WD-1 & WD-6 Warranty : 10-Year Limited

US6743029 US8684771

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

