

ENGLISH

Datasheet

RS Pro Flat Ribbon Cable Interface Module, DIN Rail Mount, Male, 14 Pole, 125 V ac/dc, 1A, 46mm

RS Stock No: 665-9651



Product Details

RS Pro flat ribbon cable interface module has a male plug with 14 contacts to support 14 to 22 AWG flat ribbon cable connection of EN 60 603-13/DIN 41651 specification. This module features an compact design with clear termination labelling and simple assembly. It features an ejector mechanism for cable removal. The module has an insulating stripping length of 7 mm. It is the best alternative to pure individual wire approach. It measures $47 \times 46 \times 61 \text{ mm}$.

Features and Benefits

- Screw clamp connection
- Male plug flat ribbon cable connection EN 60 603-13/DIN 41651
- DIN EN 50178; DIN VDE 0110, pollution degree 2
- Ejector mechanism
- Compact design, clear terminal labelling and simple assembly
- Insulating stripping length 7 mm
- Alternative to pure individual wire approach



ENGLISH

Specifications:

1	
Cable CSA	0.2 to 2.5 mm ²
Connector Type	Flat Ribbon Cable
Current Rating	1 A
Depth	47 mm
Dimensions	46 x 61 x 47 mm
Gender	Male
Length	46 mm
Maximum Operating Temperature	+50°C
Minimum Operating Temperature	-20°C
Mounting Type	DIN Rail Mount
Number of Contacts	14
Test Proof Voltage	0.67 kV ac
Voltage Rating	125 V ac/dc
Width	61 mm
Wire Size	22 to 14 AWG
Number of Poles	14