

### DDR2 SO DIMM

TE Internal #: 1473006-4 SO DIMM Sockets, Double Data Rate (DDR) 2, Stack Height .205 in [5.2 mm], Right Angle Module Orientation, 200 Position, DDR2 SO DIMM

### View on TE.com >

Connectors > Socket Connectors > Memory Sockets > SO DIMM Sockets > DDR2 SO DIMM Sockets



DRAM Type: Double Data Rate (DDR) 2

Stack Height: 5.2 mm [.205 in ]

Module Orientation: Right Angle

Connector System: Cable-to-Board

Number of Positions: 200

All DDR2 SO DIMM Sockets (30)



### Features

Product Type Features
-----------------------

DRAM Type	Double Data Rate (DDR) 2
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Bays	2
Number of Keys	1
Number of Rows	2
Module Orientation	Right Angle
Number of Positions	200
Electrical Characteristics	
DRAM Voltage	1.8 V
Signal Characteristics	

**C** For support call+1 800 522 6752

11/22/2022 04:43AM | Page 1

SO DIMM Sockets, Double Data Rate (DDR) 2, Stack Height .205 in [5.2 mm], Right Angle Module Orientation, 200 Position, DDR2 SO DIMM



SGRAM Voltage	1.8 V
Body Features	
Ejector Location	Both Ends
Latch Material	Stainless Steel
Latch Plating Material	Tin
Module Key Type	SGRAM
Ejector Type	Locking
Connector Profile	Standard
Contact Features	
Memory Socket Type	Memory Card
PCB Contact Termination Area Plating Material	Gold Flash
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold Flash
Contact Current Rating (Max)	.5 A
Termination Features	
Insertion Style	Cam-In
Mechanical Attachment	

Mating Alignment Type	Reverse Keying
PCB Mounting Style	Surface Mount
PCB Mount Retention	With
PCB Mount Retention Type	Solder Peg
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	High Temperature Thermoplastic
Housing Color	Black
Centerline (Pitch)	.6 mm[.024 in]
Dimensions	
Stack Height	5.2 mm[.205 in]
Row-to-Row Spacing	6.2 mm[.244 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	

SO DIMM Sockets, Double Data Rate (DDR) 2, Stack Height .205 in [5.2 mm], Right Angle Module Orientation, 200 Position, DDR2 SO DIMM



Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	20
Packaging Method	Semi-Hard Tray Assembly

### Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Free

### Solder Process Capability

Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## **Compatible Parts**

SO DIMM Sockets, Double Data Rate (DDR) 2, Stack Height .205 in [5.2 mm], Right Angle Module Orientation, 200 Position, DDR2 SO DIMM





# Also in the Series DDR2 SO DIMM



# Customers Also Bought



TE Part #177900-1

POWER DBL LOCK PLUG HSG 4P

TE Part #1318108-1

DYNAMIC D-2000 REC CONT S L/P

TE

TE Part #1-1623788-2

SQM5 2R2 5% (WIRE)



TE Part #171826-3

3P POST HEADER ASSY EI

TE Part #1-917337-2

DYNAMIC D-3 VERTI. HDR ASSY 2P



SO DIMM Sockets, Double Data Rate (DDR) 2, Stack Height .205 in [5.2 mm], Right Angle Module Orientation, 200 Position, DDR2 SO DIMM



### Documents

Product Drawings SEMI-HARD TRAY DDR2 SODIMM SOCKET 200P 5

English

### **CAD** Files

Customer View Model

ENG\_CVM\_CVM\_1473006-4\_M1.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_CVM\_1473006-4\_M1.2d\_dxf.zip

English

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_1473006-4\_M1.3d\_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

**Product Specification** 

English

Product Environmental Compliance

**TE Material Declaration** 

English