5-747904-8 ACTIVE

AMPLIMITE

TE Internal #: 5-747904-8

Solder D-Sub Connectors, Plug, Cable-to-Board, 9 Position, Size 20, Size 1, Shielded, Mating Retention, .11 in [2.77 mm] Centerline

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > Solder D-Sub Connectors



Connector & Housing Type: Plug
Connector System: Cable-to-Board

Number of Positions: 9
D-Sub Contact Size: 20
D-Sub Shell Size: 1

Features

Product Type Features

Grade	Standard
Grounding Indents	With
Product Type	Connector
Shell Type	Full Metal Shell
Connector & Housing Type	Plug
Connector System	Cable-to-Board
D-Sub Shell Size	1
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Preloaded	Yes
Number of Positions	9

Body Features

Shell Material	Steel
Color	Black
Insert Material	Thermoplastic
Shell Plating Material	Tin

Contact Features

Contact Type	Pin
--------------	-----



	.8 μin
Contact Mating Area Plating Material	Gold Flash
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin-Copper
Contact Base Material	Phosphor Bronze
D-Sub Contact Size	20
Contact Current Rating (Max)	3 A
Termination Features	
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
Mounting Angle	Straight
PCB Mount Retention Type	None
Mating Retention	With
Mating Retention Type	Clinch Nut, 4-40 UNC
Connector Mounting Type	Board Mount
Housing Features	
Enclosure	Without
Centerline (Pitch)	2.77 mm[.11 in]
Dimensions	
Wire Size	.5 – .6 mm²
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Shielded	Yes
Circuit Application	Signal
Industry Standards	
Insert Flammability Rating	UL 94V-0
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Hand solderable with lead free solder

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought























Documents

Product Drawings

9 Plug Solder Cup, G/F w/ CN,

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-747904-8_V_c-5-747904-8-v.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-747904-8_V_c-5-747904-8-v.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-747904-8_V_c-5-747904-8-v.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Solder D-Sub Connectors, Plug, Cable-to-Board, 9 Position, Size 20, Size 1, Shielded, Mating Retention, .11 in [2.77 mm] Centerline



Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English

UL Report

English