


# Proximity sensors

## SDBT-MSX-1L-PU-E-0.3-N-M8

Part number: 8059120

FESTO



## Data sheet

Feature	Value
Design	for T-slot
Based on norm	EN 60947-5-2
Symbol	00995962
Certification	RCM compliance mark c UL us - Listed (OL)
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
KC characters	KC EMC
Certificate issuing authority	UL E232949
Note on materials	RoHS-compliant Halogen-free
Measured variable	Position
Measuring principle	Magnetic Hall
Ambient temperature	-40 °C ... 85 °C
Max. travel speed	3 m/s
Repetition accuracy	0.1 mm
Switching output	PNP/NPN switchable
Switching element function	N/C contact/N/O contact switchable
Hysteresis	0.2 mm
On time	≤2 ms
Switch-off time	≤2 ms
Max. switching frequency	200 Hz
Max. output current	100 mA
Max. output current in mounting kits	100 mA
Max. switching capacity DC	2.8 W
Max. switching capacity DC in mounting kits	2.8 W
Voltage drop	<1.5 V
Minimum load current	0.15 mA
Residual current	<0.2 mA
Short-circuit protection	yes
Overload protection	Available
Rated operating voltage DC	24 V
DC operating voltage range	10 V ... 30 V
Reverse polarity protection	for all electrical connections
Electrical connection 1, connection type	Cable with plug

Feature	Value
Electrical connection 1, connection technology	M8x1 A-coded as per EN 61076-2-104
Electrical connection 1, number of pins/wires	3
Electrical connection 1, type of mounting	Screw-type lock
Electrical connection for input 1, connection pattern	00991155
Connection outlet orientation	Longitudinal
Connector cable test conditions	Flexural strength: as per Festo standard Test conditions on request Cable chain: 5 million cycles, bending radius 28 mm Torsional resistance: > 300 000 cycles, ±270°/0.1 m
Cable length	0.3 m
Cable characteristic	Suitability for energy chains/robot applications
Color cable sheath	Gray
Material of cable sheath	TPE-U(PUR)
Type of mounting	Screwed tightly Can be inserted in slot from above
Max. tightening torque	0.6 Nm
Mounting position	Any
Product weight	10 g
Housing colour	Black
Housing material	Brass, nickel-plated PA-reinforced High-alloy stainless steel
Switching status indication	LED yellow
Status indicator	LED green
Setting options	Auto teach-in Capacitive pushbutton
Ambient temperature with flexible cable installation	-20 °C ... 85 °C
Degree of protection	IP68
LABS (PWIS) conformity	VDMA24364-B2-L