

[TopPage](#)>>[Search Result](#)>>6012ZZE

# Deep-groove Ball Bearings

Bearing No. : **NACHI 6012ZZE**

**Bearing Type** 
**Clearance** 
**Tolerance Class**

(0.008~0.028)

<p>Dimensions</p> <p>d = 60 <span style="margin-left: 20px;">0</span>  <span style="margin-left: 20px;">-0.015</span></p> <p>D = 95 <span style="margin-left: 20px;">0</span>  <span style="margin-left: 20px;">-0.015</span></p> <p>B = 18 <span style="margin-left: 20px;">0</span>  <span style="margin-left: 20px;">-0.150</span></p> <p>r = 1.1~2          (Radial Direction)</p> <p>r = 1.1~3.5          (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 66</p> <p>Da(max) = 89</p> <p>ra(max) = 1</p> <p>Mass = 0.418 kg</p>
--	--	---

<p>Basic Dynamic Load Rating Cr : <b>29,400</b> N</p> <p>Basic Static Load Rating Cor : <b>23,200</b> N</p> <p>Limiting Speed ;</p> <p style="margin-left: 20px;">Grease Lubrication : <b>7,100</b> min<sup>-1</sup></p> <p style="margin-left: 20px;">Oil Lubrication : - min<sup>-1</sup></p>	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Width Variation :</td> <td><b>0.025</b></td> <td><b>0.025</b></td> </tr> <tr> <td>Radial Runout :</td> <td><b>0.020</b></td> <td><b>0.035</b></td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	<b>0.025</b>	<b>0.025</b>	Radial Runout :	<b>0.020</b>	<b>0.035</b>
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	<b>0.025</b>	<b>0.025</b>																	
Radial Runout :	<b>0.020</b>	<b>0.035</b>																	