

[TopPage](#)>>[Search Result](#)>>6011-2NSE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6011-2NSE**

Bearing Type
Clearance
Tolerance Class

(0.008~0.028)

<p>Dimensions</p> <p>d = 55 $\begin{matrix} 0 \\ -0.015 \end{matrix}$</p> <p>D = 90 $\begin{matrix} 0 \\ -0.015 \end{matrix}$</p> <p>B = 18 $\begin{matrix} 0 \\ -0.150 \end{matrix}$</p> <p>r = 1.1~2 (Radial Direction)</p> <p>r = 1.1~3.5 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 61</p> <p>Da(max) = 84</p> <p>ra(max) = 1</p> <p>Mass = 0.384 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : 28,300 N</p> <p>Basic Static Load Rating Cor : 21,300 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 4,500 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : - min⁻¹</p>	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td></td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td></td> </tr> <tr> <td>Width Variation :</td> <td>0.025</td> <td>0.025</td> </tr> <tr> <td>Radial Runout :</td> <td>0.020</td> <td>0.035</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	0.025	0.025	Radial Runout :	0.020	0.035
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-																		
Width Variation :	0.025	0.025																	
Radial Runout :	0.020	0.035																	