

[TopPage](#)>>[Search Result](#)>>6009-2NSE9

Deep-groove Ball Bearings

Bearing No. : **NACHI 6009-2NSE9**

Bearing Type
Clearance
Tolerance Class

(0.006~0.023)

<p>Dimensions</p> <p>d = 45 $\begin{matrix} 0 \\ -0.012 \end{matrix}$</p> <p>D = 75 $\begin{matrix} 0 \\ -0.013 \end{matrix}$</p> <p>B = 16 $\begin{matrix} 0 \\ -0.120 \end{matrix}$</p> <p>r = 1~1.5 (Radial Direction)</p> <p>r = 1~3 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 50</p> <p>Da(max) = 70</p> <p>ra(max) = 1</p> <p>Mass = 0.246 kg</p>																			
<p>Basic Dynamic Load Rating Cr : 20,900 N</p> <p>Basic Static Load Rating Cor : 15,200 N</p> <p>Limiting Speed ;</p> <p>Grease Lubrication : 5,400 min⁻¹</p> <p>Oil Lubrication : - min⁻¹</p>		<table border="1"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td></td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td></td> </tr> <tr> <td>Width Variation :</td> <td>0.020</td> <td>0.020</td> </tr> <tr> <td>Radial Runout :</td> <td>0.015</td> <td>0.025</td> </tr> </tbody> </table>			INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	0.020	0.020	Radial Runout :	0.015	0.025
	INNER RING	OUTER RING																			
O.D.Surface Runout with Side :		-																			
Axial Runout with Bore :	-																				
Axial Runout with Raceway :	-																				
Width Variation :	0.020	0.020																			
Radial Runout :	0.015	0.025																			

[Back](#)

[Calc](#)

[DXF](#)

[Print](#)