

[TopPage](#)>>[Search Result](#)>>6203ZZE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6203ZZE**

Bearing Type
 Clearance
 Tolerance Class

(0.003~0.018)

<p>Dimensions</p> <p>d = 17 0 -0.008</p> <p>D = 40 0 -0.011</p> <p>B = 12 0 -0.120</p> <p>r = 0.6~1 (Radial Direction)</p> <p>r = 0.6~2 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 22</p> <p>Da(max) = 35</p> <p>ra(max) = 0.6</p> <p>Mass = 0.065 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : 9,550 N</p> <p>Basic Static Load Rating Cor : 4,800 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 18,000 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : - min⁻¹</p>	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">0.020</td> <td style="text-align: center;">0.020</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">0.010</td> <td style="text-align: center;">0.020</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.020	0.020	Radial Runout :	0.010	0.020
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.020	0.020																	
Radial Runout :	0.010	0.020																	

[Back](#)
[Calc](#)
[DXF](#)
[Print](#)