

[TopPage](#)>>[Search Result](#)>>6000ZZE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6000ZZE**

Bearing Type
Clearance
Tolerance Class

(0.002~0.013)

<p>Dimensions</p> <p>d = 10 ⁰_{-0.008}</p> <p>D = 26 ⁰_{-0.009}</p> <p>B = 8 ⁰_{-0.120}</p> <p>r = 0.3~0.6 (Radial Direction)</p> <p>r = 0.3~1 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 12</p> <p>Da(max) = 24</p> <p>ra(max) = 0.3</p> <p>Mass = 0.019 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : 4,550 N</p> <p>Basic Static Load Rating Cor : 1,970 N</p> <p>Limiting Speed ;</p> <p>Grease Lubrication : 30,000 min⁻¹</p> <p>Oil Lubrication : - min⁻¹</p>	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td></td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td></td> </tr> <tr> <td>Width Variation :</td> <td>0.015</td> <td>0.015</td> </tr> <tr> <td>Radial Runout :</td> <td>0.010</td> <td>0.015</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	0.015	0.015	Radial Runout :	0.010	0.015
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-																		
Width Variation :	0.015	0.015																	
Radial Runout :	0.010	0.015																	