

[TopPage](#)>>[Search Result](#)>>6015-2NSE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6015-2NSE**

Bearing Type
Clearance
Tolerance Class

(0.010~0.030)

<p>Dimensions</p> <p>d = 75 0 -0.015</p> <p>D = 115 0 -0.015</p> <p>B = 20 0 -0.150</p> <p>r = 1.1~2 (Radial Direction)</p> <p>r = 1.1~3.5 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 81</p> <p>Da(max) = 109</p> <p>ra(max) = 1</p> <p>Mass = 0.645 kg</p>
---	--	--

<p>Basic Dynamic Load Rating Cr : 39,500 N</p> <p>Basic Static Load Rating Cor : 33,500 N</p> <p>Limiting Speed ;</p> <p> Grease Lubrication : 3,400 min⁻¹</p> <p> Oil Lubrication : - min⁻¹</p>	<table border="0"> <tr> <td></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td style="text-align: center;">-</td> </tr> <tr> <td> Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td></td> </tr> <tr> <td> Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td></td> </tr> <tr> <td> Width Variation :</td> <td style="text-align: center;">0.025</td> <td style="text-align: center;">0.025</td> </tr> <tr> <td> Radial Runout :</td> <td style="text-align: center;">0.020</td> <td style="text-align: center;">0.035</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	0.025	0.025	Radial Runout :	0.020	0.035
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-																		
Width Variation :	0.025	0.025																	
Radial Runout :	0.020	0.035																	