

[TopPage](#)>>[Search Result](#)>>6008ZZE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6008ZZE**

Bearing Type Two shields
Clearance CN(Normal)
Tolerance Class Normal Class
 (0.006~0.020)

Dimensions d = 40 0 -0.012 D = 68 0 -0.013 B = 15 0 -0.120 r = 1~1.5 (Radial Direction) r = 1~3 (Axial Direction)		Dimensions da(min) = 45 Da(max) = 63 ra(max) = 1 Mass = 0.194 kg
---	--	--

Basic Dynamic Load Rating Cr : 16,800 N Basic Static Load Rating Cor : 11,500 N Limiting Speed ; Grease Lubrication : 10,000 min ⁻¹ Oil Lubrication : - min ⁻¹	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Width Variation :</td> <td>0.020</td> <td>0.020</td> </tr> <tr> <td>Radial Runout :</td> <td>0.015</td> <td>0.025</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.020	0.020	Radial Runout :	0.015	0.025
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.020	0.020																	
Radial Runout :	0.015	0.025																	

Back
> Calc
> DXF
Print