

[TopPage](#)>>[Search Result](#)>>6210ZZE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6210ZZE**

Bearing Type
 Clearance
 Tolerance Class

(0.006~0.023)

<p>Dimensions</p> <p>d = 50 0 -0.012</p> <p>D = 90 0 -0.015</p> <p>B = 20 0 -0.120</p> <p>r = 1.1~2 (Radial Direction)</p> <p>r = 1.1~3.5 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 57</p> <p>Da(max) = 83</p> <p>ra(max) = 1</p> <p>Mass = 0.463 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : 35,000 N</p> <p>Basic Static Load Rating Cor : 23,200 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 7,100 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : - min⁻¹</p>	<table border="0" style="width: 100%;"> <tr> <td></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">0.020</td> <td style="text-align: center;">0.020</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">0.015</td> <td style="text-align: center;">0.035</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.020	0.020	Radial Runout :	0.015	0.035
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.020	0.020																	
Radial Runout :	0.015	0.035																	