

[TopPage](#)>>[Search Result](#)>>6013-2NSE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6013-2NSE**

Bearing Type
Clearance
Tolerance Class

 (0.008~0.028)

Dimensions d = 65 0 -0.015 D = 100 0 -0.015 B = 18 0 -0.150 r = 1.1~2 (Radial Direction) r = 1.1~3.5 (Axial Direction)		Dimensions da(min) = 71 Da(max) = 94 ra(max) = 1 Mass = 0.438 kg
--	--	--

Basic Dynamic Load Rating Cr : 30,500 N Basic Static Load Rating Cor : 25,200 N Limiting Speed ; Grease Lubrication : 4,000 min ⁻¹ Oil Lubrication : - min ⁻¹	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Width Variation :</td> <td>0.025</td> <td>0.025</td> </tr> <tr> <td>Radial Runout :</td> <td>0.020</td> <td>0.035</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.025	0.025	Radial Runout :	0.020	0.035
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.025	0.025																	
Radial Runout :	0.020	0.035																	