

[TopPage](#)>>[Search Result](#)>>6000

Deep-groove Ball Bearings

Bearing No. : **NACHI 6000**

Bearing Type
Clearance
Tolerance Class

(0.002~0.013)

Dimensions

d = 10 ⁰_{-0.008}

D = 26 ⁰_{-0.009}

B = 8 ⁰_{-0.120}

r = 0.3~0.6
(Radial Direction)

r = 0.3~1
(Axial Direction)

Dimensions

da(min) = 12

Da(max) = 24

ra(max) = 0.3

Mass = 0.019 kg

<p>Basic Dynamic Load Rating Cr : 4,550 N</p> <p>Basic Static Load Rating Cor : 1,970 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 30,000 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : 36,000 min⁻¹</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">INNER RING</th> <th style="text-align: center;">OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">0.015</td> <td style="text-align: center;">0.015</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">0.010</td> <td style="text-align: center;">0.015</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.015	0.015	Radial Runout :	0.010	0.015
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.015	0.015																	
Radial Runout :	0.010	0.015																	

[Back](#)
[Calc](#)
[DXF](#)
[Print](#)