

[TopPage](#)>>[Search Result](#)>>6001-2NSE9

# Deep-groove Ball Bearings

Bearing No. : **NACHI 6001-2NSE9**

**Bearing Type** 
**Clearance** 
**Tolerance Class**

(0.003~0.018)

<p>Dimensions</p> <p>d = 12 <sup>0</sup><sub>-0.008</sub></p> <p>D = 28 <sup>0</sup><sub>-0.009</sub></p> <p>B = 8 <sup>0</sup><sub>-0.120</sub></p> <p>r = 0.3~0.6 (Radial Direction)</p> <p>r = 0.3~1 (Axial Direction)</p>			<p>Dimensions</p> <p>da(min) = 14</p> <p>Da(max) = 26</p> <p>ra(max) = 0.3</p> <p>Mass = 0.023 kg</p>
---	--	--	---

<p>Basic Dynamic Load Rating Cr : <b>5,100</b> N</p> <p>Basic Static Load Rating Cor : <b>2,390</b> N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : <b>18,000</b> min<sup>-1</sup></p> <p style="padding-left: 20px;">Oil Lubrication : - min<sup>-1</sup></p>	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td>-</td> </tr> <tr> <td>Width Variation :</td> <td><b>0.020</b></td> <td><b>0.020</b></td> </tr> <tr> <td>Radial Runout :</td> <td><b>0.010</b></td> <td><b>0.015</b></td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	<b>0.020</b>	<b>0.020</b>	Radial Runout :	<b>0.010</b>	<b>0.015</b>
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	<b>0.020</b>	<b>0.020</b>																	
Radial Runout :	<b>0.010</b>	<b>0.015</b>																	

[Back](#)

[Calc](#)

[DXF](#)

[Print](#)