

[TopPage](#)>>[Search Result](#)>>6002ZZE

# Deep-groove Ball Bearings

Bearing No. : **NACHI 6002ZZE**

**Bearing Type** 
**Clearance** 
**Tolerance Class**

(0.003~0.018)

<p>Dimensions</p> <p>d = 15 <sup>0</sup><sub>-0.008</sub></p> <p>D = 32 <sup>0</sup><sub>-0.011</sub></p> <p>B = 9 <sup>0</sup><sub>-0.120</sub></p> <p>r = 0.3~0.6 (Radial Direction)</p> <p>r = 0.3~1 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 17</p> <p>Da(max) = 30</p> <p>ra(max) = 0.3</p> <p>Mass = 0.032 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : <b>5,600</b> N</p> <p>Basic Static Load Rating Cor : <b>2,840</b> N</p> <p>Limiting Speed ;</p> <p>Grease Lubrication : <b>24,000</b> min<sup>-1</sup></p> <p>Oil Lubrication : - min<sup>-1</sup></p>	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td>-</td> <td></td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td>-</td> <td></td> </tr> <tr> <td>Width Variation :</td> <td><b>0.020</b></td> <td><b>0.020</b></td> </tr> <tr> <td>Radial Runout :</td> <td><b>0.010</b></td> <td><b>0.020</b></td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	<b>0.020</b>	<b>0.020</b>	Radial Runout :	<b>0.010</b>	<b>0.020</b>
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-																		
Width Variation :	<b>0.020</b>	<b>0.020</b>																	
Radial Runout :	<b>0.010</b>	<b>0.020</b>																	