

[TopPage](#)>>[Search Result](#)>>6208ZZE

# Deep-groove Ball Bearings

Bearing No. : **NACHI 6208ZZE**

**Bearing Type** 
**Clearance** 
**Tolerance Class**

(0.006~0.020)

<p>Dimensions</p> <p>d = 40     0            -0.012</p> <p>D = 80     0            -0.013</p> <p>B = 18     0            -0.120</p> <p>r = 1.1~2 (Radial Direction)</p> <p>r = 1.1~3.5 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 47</p> <p>Da(max) = 73</p> <p>ra(max) = 1</p> <p>Mass = 0.366 kg</p>
--	--	---

<p>Basic Dynamic Load Rating Cr :     <b>29,100</b> N</p> <p>Basic Static Load Rating Cor :     <b>17,900</b> N</p> <p>Limiting Speed ;</p> <p>    Grease Lubrication :     <b>8,700</b> min<sup>-1</sup></p> <p>    Oil Lubrication :     - min<sup>-1</sup></p>	<table border="0"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td>    Axial Runout with Bore :</td> <td>-</td> <td></td> </tr> <tr> <td>    Axial Runout with Raceway :</td> <td>-</td> <td></td> </tr> <tr> <td>    Width Variation :</td> <td><b>0.020</b></td> <td><b>0.020</b></td> </tr> <tr> <td>    Radial Runout :</td> <td><b>0.015</b></td> <td><b>0.025</b></td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	<b>0.020</b>	<b>0.020</b>	Radial Runout :	<b>0.015</b>	<b>0.025</b>
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-																		
Width Variation :	<b>0.020</b>	<b>0.020</b>																	
Radial Runout :	<b>0.015</b>	<b>0.025</b>																	

[Back](#)

[Calc](#)

[DXF](#)

[Print](#)