

[TopPage](#)>>[Search Result](#)>>6001ZZE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6001ZZE**

Bearing Type
Clearance
Tolerance Class

(0.003~0.018)

<p>Dimensions</p> <p>d = 12 ⁰_{-0.008}</p> <p>D = 28 ⁰_{-0.009}</p> <p>B = 8 ⁰_{-0.120}</p> <p>r = 0.3~0.6 (Radial Direction)</p> <p>r = 0.3~1 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 14</p> <p>Da(max) = 26</p> <p>ra(max) = 0.3</p> <p>Mass = 0.023 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : 5,100 N</p> <p>Basic Static Load Rating Cor : 2,390 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 28,000 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : - min⁻¹</p>	<table border="0"> <thead> <tr> <th></th> <th style="text-align: center;">INNER RING</th> <th style="text-align: center;">OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td></td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">0.020</td> <td style="text-align: center;">0.020</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">0.010</td> <td style="text-align: center;">0.015</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-	-	Width Variation :	0.020	0.020	Radial Runout :	0.010	0.015
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-	-																	
Width Variation :	0.020	0.020																	
Radial Runout :	0.010	0.015																	