

[TopPage](#)>>[Search Result](#)>>6204ZZE

Deep-groove Ball Bearings

Bearing No. : **NACHI 6204ZZE**

Bearing Type
 Clearance
 Tolerance Class

(0.005~0.020)

<p>Dimensions</p> <p>d = 20 0 -0.010</p> <p>D = 47 0 -0.011</p> <p>B = 14 0 -0.120</p> <p>r = 1~1.5 (Radial Direction)</p> <p>r = 1~3 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 26</p> <p>Da(max) = 41</p> <p>ra(max) = 1</p> <p>Mass = 0.106 kg</p>
---	--	---

<p>Basic Dynamic Load Rating Cr : 12,800 N</p> <p>Basic Static Load Rating Cor : 6,600 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 16,000 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : - min⁻¹</p>	<table border="0" style="width: 100%;"> <tr> <td></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">0.020</td> <td style="text-align: center;">0.020</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">0.013</td> <td style="text-align: center;">0.020</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.020	0.020	Radial Runout :	0.013	0.020
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.020	0.020																	
Radial Runout :	0.013	0.020																	

[Back](#)
[Calc](#)
[DXF](#)
[Print](#)