

Coaxial Cable Connector 11_MMBX-50-2-1/111_N

Description

Straight cable plug

Interface standards
SUHNER-MMBX



Technical Data

Electrical Data

| | |
|--------------------------|----------|
| Impedance | 50 Ω |
| Interface frequency max. | 12.4 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | crimped |
| Outer contact | crimped |
| Weight | 0.0007 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -55 °C to 155 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|--------------------------|--|
| Centre contact | Copper Beryllium / Brass | Gold Plating (Nickel underplated) |
| Outer contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Body | Brass | SUCOPRO Plating |
| Insulator | PFA / PTFE | |
| Crimp ferrule | Copper | Gold Plating (without Nickel underplating) |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00006163 |
| Catalogue drawing | DOU-00006165 |
| Assembly instruction | DOC-0000179377 |

Ordering Information

| | |
|----------------|-----------------------|
| Single package | 11_MMBX-50-2-1/111_NE |
|----------------|-----------------------|

Additional Information

| | |
|-----------------|----------------------------------|
| Suitable cables | RG_316_/U, RG_188_A/U, RG_174_/U |
|-----------------|----------------------------------|